



P.O. Box 1719
Corona, CA 92878
Support: 951-493-7100
www.aFeFilters.com

Intake Kit Installation Instructions: 94-01 Dodge Ram Trucks V8-5.2L & 5.9L Stage-2 Air Intake

Kit Part #	51/54-10112		Tools Required: 1/4" socket, nut-driver 5/16" socket, nut-driver 7/16" socket, nut-driver 13mm socket or wrench Ratchet and extension Med flat screwdriver Small flat screwdriver	Part List: 1 Filter Part # (24-90025 or or Pro Dry S™ 21-90025) 1 Filter Housing 1 Intake tube 1 Cap, throttle body 1 5/8" hose @ 23" 2 Clamp, mini #008 1 3/4 Trim seal @ 31.5"	1 7/16" Trim seal @ 14.25"
Make:	Dodge				1 Bracket, sub-assembly.
Model	Year	Engine			1 Coupling, straight, (3-1/2" x 3-3/4")ID x 3"L
Ram	'94-'01	V8-5.2L			2 Clamp, #060
Ram	'94-'01	V8-5.9L			1 Nut, wing, 1/4-20"
					1 Washer, fender 1/4-20"
					1 Retainer, push
					1 Screw, carriage 1/4-20" x 3/4"
					1 Screw, hex flange 1/4-20" x 3/4"
					1 Spacer, 3/8" x 1.63"



Step 1

Complete kit with parts.



Step 2

Complete stock intake.



Step 3

Remove air duct from resonator box and completely remove from engine compartment.



Step 4

Loosen clamp at resonator box for throttle body and disconnect vent hose at valve cover.



Step 5

Once clamp is loose, pull up and out. Reuse existing gasket.



Step 6

Install throttle body cap hold down bracket assembly.



Step 7

Assemble throttle body cap with straight coupler and vent hose.



Step 8

Install throttle cap stand off spacer (arrow) and cap. Reuse original throttle body gasket.



Step 9

Remove three inner-fender bolts (13mm socket or wrench) for attachment of filter housing.



Step 10

Install large housing trim seal to top of housing and small trim seal to tube inlet. Attach filter housing to inner fender-well with the three specified bolts.



Step 11

Insert tube through filter housing and attach to coupler with supplied clamps.



Step 12

Attach filter to intake tube. It may be a tight fit, but DO NOT OIL OR GREASE TO INSTALL.



Step 13

Make sure all hoses and clamps are tight and that all electrical components are secure.